

Project: _____

Type: _____

Quantity: _____



The SRM Series is an ideal choice for curved roads, bicycle/walking paths, rural traffic and as lane delineation. The SRM Series high performance Internally Illuminated Recessed Pavement Marker (IIRPM) offers years of reliable, cost-effective roadway safety. Made of virtually indestructible cast aluminum, the SRM is IP68 rated and fabricated to withstand heavy vehicles and even snowplows. Installation is simple - a hole and epoxy ensure maintenance-free, grid-independent service.

The SRM Series (IIRPM) is an ideal choice for:

- Rural roads
- Cycling/walking paths
- Lane delineation
- Visibility in inclement weather
- Providing path and road illumination safety



Thanks to First Light's innovative solar technology, there are no wires to install, no batteries to replace and virtually no maintenance.

TECHNICAL SPECIFICATIONS

Storage Technology	Pseudocapacitor
Full Sun Charge Time	3 Hours
Overcast Charge Time	8 Hours
Discharge Time	Up to 16 Hours
Snowplowable	Yes
Housing Material	Cast Aluminum
Lens Material	Polycarbonate

Compressive Strength	(LBF) 239,000 N
Operating Temperature	-40F to 158F
LED Direction	Uni or Dual
Seal Rating	IP68
Activation	Dusk-to-Dawn
Color Options	Yellow/Blue, Red, Green, Blue, Yellow
Function Options	Steady, Slow Flash, Fast Flash
Dimensions	Ø5.38" x 1.97"

ORDER MATRIX

Series	Lighting Profile	Distribution	Color	Function
SRM	00 - Dusk-to-Dawn	D1 - Uni	YB - Yellow/Blue	S - Steady
		D2 - Dual	RD - Red	SF - Slow Flash
			GR - Green	FF - Fast Flash
		BL - Blue		
		YW - Yellow		