

3 STEPS

WE TAKE TO GUARANTEE OUR EVERGEN WILL PERFORM AS PROMISED:

Engineer a system that meets required light levels.

We design it smart, not large, to ensure cost savings.

Build it tough to withstand heat, cold, wind, and moisture.

We offer a 10-year standard warranty.*

Accurately size for each location. We guarantee light performance over the long term as planned.

^{*5-}year warranty on standard battery. Extended-life 10-year battery upgrade available.

EVERGEN® TECHNICAL SPECIFICATIONS



| SOLAR PANEL | 1 Battery | | 2 Batteries | | 3 Batteries | | 4 Batteries | |
|-------------|-------------|--------------|-------------|--------------|-------------|--------------|-------------|--------------|
| | EPA (sq ft) | Weight (lbs) |
| Single | 7.33 | 145 | 8.18 | 215 | 8.18 | 273 | 8.18 | 331 |
| Double | 14.67 | 174 | 15.52 | 243 | 15.52 | 301 | 15.52 | 360 |

^{*} Luminaire and arm not included. System weight and EPA will vary based on the number and type of both fixtures and batteries. The chart above is for reference only. Sol provides a calculated EPA and weight when a system is quoted and submitted.

| SYSTEM DATA | | | | | |
|---------------------------|--|--|--|--|--|
| Colors | Aluminum/silver (natural finish), black, bronze. Custom RAL colors available upon request. | | | | |
| Material | Grade A corrosion resistant aluminum for panel mounts and battery enclosure. Steel and aluminum poles available. | | | | |
| Security | Batteries mounted at the top of pole to reduce theft and vandalism. Security bolts used to fasten cover. | | | | |
| Options | Decorative painted panel pan | | | | |
| Pole Tenon | 3.5" (88.9mm) O.D. x 6" (152.4mm) | | | | |
| Panel Quantity | 1–2 based on sizing | | | | |
| CONTROLLER | | | | | |
| Monitoring | Remote monitoring package | | | | |
| Charging Type | MPPT | | | | |
| LED Fixture Power | Via integrated onboard high-efficiency driver | | | | |
| Operating Profile Options | Dusk-to-dawn 100% power, various dimmed profiles | | | | |
| Day/Night Transition | Via solar panels | | | | |
| BATTERY | | | | | |
| Туре | Maintenance-free valve regulated lead acid; spill-proof, leak-proof. | | | | |
| Standard Options | Gel Technology Group 27 (5-year) | | | | |
| Extended Life Options | Pure Lead AGM Technology Group 31 (10-year) | | | | |
| Quantity | 1–4 based on sizing | | | | |
| FIXTURES | | | | | |
| Туре | Cree XSP High Output Solar Series | | | | |
| IES Distribution Types | Type 2 Long, 3 Medium, 4 Medium | | | | |
| Color Temperature Options | 3000K, 4000K | | | | |
| Efficacy Range | 165 to 130 lumens per watt from complete fixture (3000K, via LM-79 testing) | | | | |
| Color Rendering Index | Minimum of 70 CRI | | | | |
| Mounting | 42mm-60mm (1.6in-2%in) OD horizontal tenon, min 203mm (8.0in) in length | | | | |

| WARRANTY (See warranty documentation for more details) | | | | | |
|--|---|--|--|--|--|
| Electronics | 10 years | | | | |
| D | 5-year warranty on standard battery | | | | |
| Battery | Up to 10-year extended-life battery upgrades available | | | | |
| Fixture | Manufacturer's Warranty – 10 years limited excluding finish | | | | |
| Pole | Lifetime (excluding finish) | | | | |
| Hardware | 10 years | | | | |

EverGEN® ENERGY MANAGEMENT SYSTEM

The EverGEN® ensures bright, reliable light output and healthy, high-functioning lighting systems with low-maintenance operation and remote monitoring.

- Bluetooth® wireless technology and setup app for simple and secure setup.
- System health notifications via email if an EverGen isn't working as expected
- Programmed by Sol based on your project requirements
- Flexible operating modes (dusk-to-dawn, split night, split night with dimming)
- Integrated MPPT charging and LED driving system reduces system failures, overall system complexity, and cost
- Integrated surge protection and noise reduction
- Keyed connectors for simple and reliable assembly
- Temperature compensated and MPPT controlled battery charging to maximize battery life and energy collection
- Rugged solid state design ensures long life and no maintenance
- 10-year limited warranty

US and International patents apply. Other patents pending. "Sol" logo is a trademark of Carmanah Technologies Corp. All Carmanah products are manufactured in facilities that are certified to ISO quality standards.

The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Sol Inc. is under license. Other trademarks and trade names are those of their respective owners.

 ${\tt Document: SELL_SOL_EverGen_RevD}$