



Our range of solar bollards are used in various applications; for safety and security lighting, to ensure compliance with the Australian Standard P4 lighting code for walkways and paths, or to simply provide ambient lighting in gardens. The modern design and robust cast aluminum construction of the Polaris solar bollard makes it ideal for use in architectural and commercial pathway projects. The light source is from 12 4000k high intensity LEDs, giving the fixture approx 200lm output. The 9v, 2.5w solar panel and 4.4v /4400mah inbuilt lithium battery, combine to enable the bollard to illuminate for 10-12 hours each night. This bollard comes in a black or grey powdercoat finish. The bollard is suitable for bolt down installation.

FEATURES

Commercial grade solar lighting

Requires 10 - 12 hrs charge prior to use

10 - 12 hours light output per night

High quality inbuilt lithium battery

Attractive modern design

Ideal for illuminating paths and walkways

Automatic light sensor turns LEDs on and off for dusk to dawn operation

Warranty: 3 year warranty for faulty workmanship or component failure not influenced by external means

Polaris Solar Bollard

Specification



Specifications

Colour	Powdercoat black or grey
Charge Time	4 - 6 hours
CCT	4000K (cool white)
Bollard Size	800H x 285Wmm
Brightness	Approx. 200 lumen output
Solar Panel	9V 2.5 watt
Solar Panel Size	125H x 140Wmm
Light Source	12 high intensity LEDs
Battery	7.4V/4400mah inbuilt lithium battery
Material	Aluminium, polycarbonate diffuser
SKU	SOLB007

